

# Battery-Operated Tools

## For plastic strapping

### Battery-Operated Friction-weld

The BXT2 combination tool applies polypropylene or polyester strapping, utilizing friction weld joint technology to join strap ends and automatic weld function which speeds up cycle time. The battery-operated BXT2 has a simple two-button process and ergonomic design to reduce operator fatigue.



BXT2-16, BXT2-19



BTS-16, 19, 25, 32\*



PT\*



Rechargeable battery pack

Model	Part Number	Strap Type Contrax, Tenax	Joint Type	Applied Tension	Description	Shipping Weight	
						lbs	kg
BXT2-16	428340	9-13 mm Contrax & Tenax 1816, 1818, 1822 (with Guide change); 816, 818, 2030, 2040, 2040H	Tension-Weld	Up to 550 lbs	Battery	9	4.1
BXT2-19	428350	2040, 2040H, 2220, 2225				Up to 880 lbs	9.3
BTS-16/PT-16 COMBO	427100	2030, 2040, 2220, 2225, 2480, 10050	Tension-Weld	Up to 800 lbs.	Battery	(BTS) 6.8 (PT) 4	3 1.8
BTS-19/PT-19 COMBO	427101						
BTS-25/PT-25 COMBO	427102						
BTS-32/PT-32 COMBO	428220						
		2625, 2680; 32mm High Strength Tenax					

\* The BTS and PT tools can be ordered separately.

## Dispensers

### For plastic strapping



DD-1A

Floor model with straproller. Can be suspended overhead.



DF-X

An all purpose, easy loading dispenser for mill wound coils.



DF-15

For typical shipping room. Easily loaded.



DF-16A

Designed for use with high-strength polyester strapping.



DF-1-12D

For power equipment. Dancer arm and brake. Base sold separately (Part No. 024360).



DO-3D

Can be suspended from a wall or ceiling.

Strap Dispenser Model	Part Number	Strap Size		Straproller	Portable	Tool tray	Dimensions						Dispenser Weight	
		inch	mm				Height		Width		Length		lbs	kg
							inch	mm	inch	mm	inch	mm		
DD-1A	024520	7/16-1/2	10.5-12	•	•	•	41	1 041	12	305	25	635	48	22
DF-X	429220	3/8-1-1/4	9.5-31.8	•	•	•	37	940	24-1/2	622	19	483	58	26.3
DF-15*	273725	3/8-3/4	10.5-19.0	•	•	•	37-3/4	959	16	406	25	635	62	28
DF-16A	422300	7/16-3/4	10.5-19.0		•	•	38	965	18	457	28-1/2	724	62	28
DF-1-12D	031318	3/8-3/4	9-19.0				36-3/4	933	12-1/2	315	47-1/4	1200	97	44
DO-3D	024500	3/8-3/4	9-19.0	•			31	787	6-3/4	171	27-3/4	705	41	19

\* Dispenser can be used with both steel and plastic strapping.

## Pneumatic tool accessories

See Page 10 for additional fittings.



Safety lockout valve

Regulator and filter

Lubricator

A filter-regulator-lubricator (FRL) assembly is needed with all pneumatic tools and equipment. Additional pneumatic accessories are available from Signode to help provide optimum operation. Please contact your Signode sales representative for more information on the proper fittings for your specific tool or equipment.

Note: Only use light weight air tool oil in lubricator, such as Non-fluid Oil No. L0713-54 (Part No. 008556) or equivalent.